

## Reax 20 - para 12 botellas (2-32rpm)

### Technical datasheet



|                                    |                                                                                                            |
|------------------------------------|------------------------------------------------------------------------------------------------------------|
| <b>Dimensions (W × H × D)</b>      | 1050 × 520 × 465                                                                                           |
| <b>Weight</b>                      | 33 kg                                                                                                      |
| <b>Maximum permissible load</b>    | 30 kg                                                                                                      |
| <b>Drive</b>                       | Asynchronous motor                                                                                         |
| <b>Speed range</b>                 | 2 – 32 rpm; Speed display: scale                                                                           |
| <b>Protection class (EN 60529)</b> | IP21                                                                                                       |
| <b>Acoustic pressure</b>           | < 45 dB (A), in accordance with IEC 61010                                                                  |
| <b>Rated voltage</b>               | 230 V, 50/60 Hz   115 V, 60 Hz                                                                             |
| <b>Protection class</b>            | I                                                                                                          |
| <b>Overvoltage category</b>        | n.a.                                                                                                       |
| <b>Degree of pollution</b>         | n.a.                                                                                                       |
| <b>Power input</b>                 | 280 W                                                                                                      |
| <b>Operating temperature</b>       | 5 °C – 31 °C at up to 80 % rel. humidity   32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly) |
| <b>Installation altitude</b>       | up to 2,000 m asl                                                                                          |
| <b>Overheat protection</b>         | self-resetting                                                                                             |
| <b>Speed control</b>               | electronic                                                                                                 |
| <b>Usable area</b>                 | n.a.                                                                                                       |
| <b>Movement</b>                    | vertically rotating                                                                                        |
| <b>Orbit</b>                       | n.a.                                                                                                       |

Fuse

T3, 15 A (230 V) | T6, 25 A (115 V)

Permissible mains voltage  
fluctuations

n.a.

Bottle dimensions

Maximum bottle diameter: 136 mm | Maximum bottle  
height: 270 mm